





D11200 x 800 mm





Art. no. 83360701

	data	

Dimensions L x W x H (mm) 1200 x 800 x 150

Weight (kg) 12.0

Material*3 HDPE, Virgin material

Load capacity (kg)*2

<u>+</u>

Static 5000



Dynamic 1000



In racking system

400

Characteristics

Colour: redbrown Runners: 3, unwelded

nullileis. 3, ullweide

Rims: 7 mm

Temperatur stability: -30 °C to +40 °C, briefly up to +90 °C

Options

Transponder

Reinforcement profiles

Rims Antislip

Loading quantities (pcs/approx.)



Container 20': 215 Container 40' High Cube: 490

Container 40': 440 Conventional trailer 45' high cube container: 544




Truck MEGA-Trailer: 646

Jumbo: 684-722

Labelling options

Customised printing and numbering available on request depending on quantity. Position upon consultation.









- *1 All technical data include characterisic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Static load: resistance to pressure on a flat ground surface and an evenly distributed load at a room temperature of approx. 20 °C Dynamic load: on a forklift with an evenly distributed load at a room temperature of approx. 20 °C.
- In racking system: evenly distributed load (sacks) along the longitudinal sides. Resting on two supports for over 100 h at a room temperature of approx. 20°C.
- *3 Although still within ISO compulsory range, the load-bearing test results using pallets made from regranulated material show slightly more variation than those from virgin HDPE.

Distributor:

Phone: +372 6030464 E-mail: info@parlmutter.com Web page: www.parlmutter.com